



GR012 Plastic Cup, 16 oz.  
078698217833

# DISC & DRUM BRAKE WHEEL BEARING GREASE

**LIQUID WRENCH® High Temperature Disc & Drum Brake Wheel Bearing Grease.** Recommended for wheel bearings and disk brakes, chassis lubrication, virtually all automotive and industrial applications. This is a non-soap polyurea lubricating grease formulated with high quality raw materials. It is fortified with rust and oxidation inhibitors as well as extreme pressure additive. This offers a dropping point of over 500°F and performs well in areas where water washout is a major concern. The chemical and physical properties make it a superb, all-purpose lubricating grease. A typical operating temperature range for the Wheel Bearing Grease is -40°F to +325°F.

### APPLICATIONS:

- Meets High Temp. Requirements of All Disc & Drum Brakes & Similar Applications

### TYPICAL PROPERTIES:

NLGI Grade: 2	Worked Penetration, 60 Strokes, ASTM D 217: 275
NLGI Certification: GC-LB	Roll Stability, % Change, ASTM D 1831: Less than 10
Thickener: Polyurea	Dropping Point, °F (°C), Min, ASTM D 2265: 500 (260)
Thickener %: 12 - 14	Oxidation Stability, 100 hrs, @ 210°F, ASTM D 942: 10 Max.
Texture: Smooth	Water Washout, % Loss @175°F, (typical) ASTM D 1264: < 5
Color: Blue Green	
Mineral Oil	
Pour Point °F: 0 - 10°F	
Viscosity @ 210°F, SUS: 76	
Viscosity @100°F, SUS: 800	
Viscosity Index, Min: 95	
Corrosion Prevention, ASTM D 1743: Pass	
Timken OK loads, lbs, ASTM D 2509: 45 Min	
Four Ball Wear, mm Scar Dia., ASTM D 2266: 0.6	
Four Ball EP Weld Point, kgf, min, ASTM D 2596: 250	

**DIRECTIONS:** Do not mix greases of different types. Thoroughly remove old grease before applying.

**DANGER:** May cause eye and skin irritation. Avoid contact with eyes and prolonged or repeated contact with skin. Wash hands after using product. May be harmful if swallowed.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room immediately.

**KEEP AWAY FROM CHILDREN AND ANIMALS**

**NOTICE:** While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.