

GAS TREATMENT

BENEFITS: Helps reduce intake valve deposits ● Helps keep clean entire fuel system ● Helps increase fuel economy ● Removes water ● Fights gas line freeze

DIRECTIONS: Treats 15 gallons of gasoline. For best results, add entire bottle contents to near empty tank and refuel. Do not refuel until tank is near empty. Use in every tank to remove moisture and improve cleaning performance of gasoline. Maintains fuel system cleanliness. AVOID CONTACT WITH PAINTED SURFACES. In case of paint contact wash off with water immediately

STORAGE, **HANDLING & DISPOSAL**: Dispose or product residue and the empty container in accordance with all local, state, and federal laws and regulations.

DANGER: HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE AND SKIN IRRITANT. COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME. USE WITH ADEQUATE VENTILATION.

FIRST AID: EYES: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. SKIN: Wash with soap and water. If irritation develops, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

M2312	Plastic Bottle, 12 fl. oz. 078698132310
M2349	Metal Drum, 54 gal. 078698132389

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

